Introduction to Experimental Design

Raj Jain

Washington University in Saint Louis

Saint Louis, MO 63130

Jain@cse.wustl.edu

These slides are available on-line at:

http://www.cse.wustl.edu/~jain/cse567-17/

Overview

❑ What is experimental design?

❑ Terminology

❑ Common mistakes

❑ Sample designs

Experimental Design and Analysis

How to:

❑ Design a proper set of experiments for measurement or simulation.

❑ Develop a model that best describes the data obtained.

❑ Estimate the contribution of each alternative to the performance.

❑ Isolate the measurement errors.

❑ Estimate confidence intervals for model parameters.

❑ Check if the alternatives are significantly different.

❑ Check if the model is adequate.

Example

Personal workstation design

1. Processor: 68000, Z80, or 8086.

2. Memory size: 512K, 2M, or 8M bytes

3. Number of Disks: One, two, three, or four

4. Workload: Secretarial, managerial, or scientific.

5. User education: High school, college, or post-graduate level.

Five **Factors** at 3x3x4x3x3 **levels**

Terminology

- **Response Variable**: Outcome.

  E.g., throughput, response time
- **Factors**: Variables that affect the response variable.

  E.g., CPU type, memory size, number of disk drives, workload used, and user's educational level.

  Also called predictor variables or predictors.
- **Levels**: The values that a factor can assume, E.g., the CPU type has three levels: 68000, 8080, or Z80.

  # of disk drives has four levels.

  Also called **treatment**.
- **Primary Factors**: The factors whose effects need to be quantified.

  E.g., CPU type, memory size only, and number of disk drives.

Terminology (Cont)

- **Secondary Factors**: Factors whose impact need not be quantified.

  E.g., the workloads.
- **Replication**: Repetition of all or some experiments.
- **Design**: The number of experiments, the factor level and number of replications for each experiment.

  E.g., Full Factorial Design with 5 replications: $3 \times 3 \times 4 \times 3 \times 3$ or 324 experiments, each repeated five times.
- **Experimental Unit**: Any entity that is used for experiments.

  E.g., users. Generally, no interest in comparing the units.
- Goal - minimize the impact of variation among the units.

Terminology (Cont)

- **Interaction** $\Rightarrow$ Effect of one factor depends upon the level of the other.

Table 1: Noninteracting Factors

	A_1	A_2
B_1	3	5
B_2	6	8

Table 2: Interacting Factors

	A_1	A_2
B_1	3	5
B_2	6	9

Common Mistakes in Experimentation

- The variation due to experimental error is ignored.
- Important parameters are not controlled.
- Effects of different factors are not isolated
- Simple one-factor-at-a-time designs are used
- Interactions are ignored
- Too many experiments are conducted.

  Better: two phases.

Types of Experimental Designs

- **Simple Designs**: Vary one factor at a time

$$\text{\# of Experiments} = 1 + \sum_{i=1}^{k} (n_i - 1)$$

  - Not statistically efficient.
  - Wrong conclusions if the factors have interaction.
  - Not recommended.
- **Full Factorial Design**: All combinations.

$$\text{\# of Experiments} = \prod_{i=1}^{k} n_i$$

  - Can find the effect of all factors.
  - Too much time and money.
  - May try 2^k design first.

Types of Experimental Designs (Cont)

- Fractional Factorial Designs: Less than Full Factorial
  - Save time and expense.
  - Less information.
  - May not get all interactions.
  - Not a problem if negligible interactions

A Sample Fractional Factorial Design

- Workstation Design:

  (3 CPUs)(3 Memory levels)(3 workloads)(3 ed levels)
  = 81 experiments

Experiment Number	CPU	Memory Level	Workload Type	Educational Level
1	68000	512K	Managerial	High School
2	68000	2M	Scientific	Post-graduate
3	68000	8M	Secretarial	College
4	Z80	512K	Scientific	College
5	Z80	2M	Secretarial	High School
6	Z80	8M	Managerial	Post-graduate
7	8086	512K	Secretarial	Post-graduate
8	8086	2M	Managerial	College
9	8086	8M	Scientific	High School

Summary

- Goal of proper experimental design is to get the maximum information with minimum number of experiments
- Factors, levels, full-factorial designs

Homework 16: Exercise 16.1

The performance of a system being designed depends upon the following three factors:

➢ CPU type: 68000, 8086, 80286

➢ Operating System type: CPM, MS-DOS, Unix

➢ Disk drive type: A, B, C

➢ How many experiments are required to analyze the performance if:

    a. There is significant interaction among factors.

    b. There is no interaction among factors.

    c. The interactions are small compared to main effects.

Scan This to Download These Slides

Raj Jain
http://rajjain.com

Related Modules

CSE567M: Computer Systems Analysis (Spring 2013),
https://www.youtube.com/playlist?list=PLjGG94etKypJEKjNAa1n_1X0bWWNyZcof

CSE473S: Introduction to Computer Networks (Fall 2011),
https://www.youtube.com/playlist?list=PLjGG94etKypJWOSPMh8Azcgy5e_10TiDw

Wireless and Mobile Networking (Spring 2016),
https://www.youtube.com/playlist?list=PLjGG94etKypKeb0nzyN9tSs_HCd5c4wXF

CSE571S: Network Security (Fall 2011),
https://www.youtube.com/playlist?list=PLjGG94etKypKvzfVtutHcPFJXumyyg93u

Video Podcasts of Prof. Raj Jain's Lectures,
https://www.youtube.com/channel/UCN4-5wzNP9-ruOzQMs-8NUw